Cost Estimates for improvement and upgrade

The Corrieyairack Pass



at Culachy, Fort Augustus

October 2003

Cost estimates for improvement and upgrade of Corrieyairick Pass Lower section at Culachy, Fort Augustus

Further to the condition survey conducted in January 2003, a request has been made by the Estate, SNH and The Highland Council for a cost estimate in relation to the work required to rectify the hazards and improve the route for recreational access.

The main points raised in the condition survey the current risks which included:

- High risk of wall collapse
- High risk of slips and falls
- Low risk of flood

The recommendations were for four main work areas to be addressed:

- Drainage
- Surface work
- Wall repair
- Vegetation clearance

Recent inspection by an experienced contractor also noted that the main drainage problems are created by failed culverts higher on the track between the deer gate and the estate entrance. Burns which were previously intercepted by these failed culverts have resulted in much greater down flow of water than the lower drainage system was intended to carry. An additional problem may be created by the overflow from the mill pond, which may create additional flow to the lower section.

It has also been noted that the culvert under the Ardachy Road and lower at the A82 will require attention in future due to flood damage and silt build up caused by the flooding of this route. This work is not be included in the estimates.

Having discussed the main issues and the result required, HAPM and Mr Cairns have produced provisional estimates for the work required. There are two options; Option 1 is for the reinstatement to allow non-motorised use, and Option 2 is for limited motorised use. It is likely that motorised use will adversely affect the sustainability of this work, and that preferred use should be non-motorised.

Option 1 estimated cost is £20,152 and Option 2 is £25,147 excl VAT, which compare favourably with the £14,000 estimated in 1993. These estimates are based on all aggregate materials for the construction being won on site from borrow pits which were used in the original construction, subject to estate approval.

DE Andrews Highland Access Project Manager 31.10.2003

Option 1 Non-motorised access.

ITEM	DESCRIPTION	UNIT	QUANTITY	RATE £	AMOUNT + VAT £
1	Between 5m-63m & 175m-286m reconstruct route of width 1.5m with 950mm as raised sub-base and 25mm graded surfacing compacted to form a 1:40 crossfall draining to ditch.	M	169	35.00	5,915.00
2	Between 63m-148m & 350m-470m scrape vegetation of width 1.5m and resurface with 75mm as raised sub-based and 25mm graded surfacing compacted to form a 1:40 crossfall draining to ditch	M	205	7.00	1,435.00
3	Between 148m-175m reconstruct route of width 1.5m with 1475mm as raised sub-base and 25mm graded surfacing compacted to form a 1:40 crossfall draining to ditch.	M	27	50.00	1,350.00
4	Between 286m-350m reconstruct route with 375mm+25mm as above.	М	64	20.00	1,280.00
5	At 109m and between 263m- 274m rebuild drystone wall to same section and dimensions as existing wall	M	13	100.00	1,300.00
6	Between 160m-175m install retaining wall to retain field edge of height 10.5m	M	15	50.00	750.00
7	At 160m and 175m renovate existing wall ends as necessary to consolidate.	No	2	100.00	200.00
8	Between 64m-148m rebuild burn side revetment as necessary to consolidate.	M²	20	50.00	1,000.00

Remove existing culvert pipes in ditch to a licensed tip. M	ITEM	DESCRIPTION	UNIT	QUANTITY	RATE	AMOUNT + VAT
encroaching vegetation and trees from route and ditch to create a clear walking tunnel of width 4m and height 3m 11 Between 0m-470m clear out/redefine and reprofile ditch sensitively to avoid damage to existing stonework and create a low profile ditch whole appropriate with vegetated sides 12 At 507m, 1040 and 1180 install 3 no. new culvert pipes (twin walled polyproplyn) of diameter 500mm and length 6m with stone loadwalls 13 At 507, 1040 and 1180 break ditch at culverts with rock arour 14 At 5m and 63m remove barrier including field gates and bollards and remove to a licensed tip. 15 Allowance for replacement of new barriers/gates. 16 Landscape route margins and disturbed ground with even battered slopes and graded margins and split turfs	9	·	M		10.00	340.00
out/redefine and reprofile ditch sensitively to avoid damage to existing stonework and create a low profile ditch whole appropriate with vegetated sides 12 At 507m, 1040 and 1180 install 3 no. new culvert pipes (twin walled polyproplyn) of diameter 500mm and length 6m with stone loadwalls 13 At 507, 1040 and 1180 break ditch at culverts with rock arour 14 At 5m and 63m remove barrier including field gates and bollards and remove to a licensed tip. 15 Allowance for replacement of new barriers/gates. 16 Landscape route margins and disturbed ground with even battered slopes and graded margins and split turfs	10	encroaching vegetation and trees from route and ditch to create a clear walking tunnel	M	324	0.50	162.00
install 3 no. new culvert pipes (twin walled polyproplyn) of diameter 500mm and length 6m with stone loadwalls 13 At 507, 1040 and 1180 break ditch at culverts with rock arour 14 At 5m and 63m remove barrier including field gates and bollards and remove to a licensed tip. 15 Allowance for replacement of new barriers/gates. 16 Landscape route margins and disturbed ground with even battered slopes and graded margins and split turfs 17 In the stone of twin walls and the stone of twin walls and the stone of twin walls and the stone of the stone	11	out/redefine and reprofile ditch sensitively to avoid damage to existing stonework and create a low profile ditch whole appropriate with	M	470	7.00	3290.00
ditch at culverts with rock arour No 2 100.00 200.00 barrier including field gates and bollards and remove to a licensed tip. Sum 500.00 Landscape route margins and disturbed ground with even battered slopes and graded margins and split turfs	12	install 3 no. new culvert pipes (twin walled polyproplyn) of diameter 500mm and length	М	18	40.00	720.00
barrier including field gates and bollards and remove to a licensed tip. Sum Allowance for replacement of new barriers/gates. Sum 500.00 Landscape route margins and disturbed ground with even battered slopes and graded margins and split turfs	13	ditch at culverts with rock	M²	6	50.00	300.00
new barriers/gates. 16 Landscape route margins and disturbed ground with even battered slopes and graded margins and split turfs 18 M² 470 3.00 1410.00	14	barrier including field gates and bollards and remove to a	No	2	100.00	200.00
disturbed ground with even battered slopes and graded margins and split turfs	15	-		Sum		500.00
	16	disturbed ground with even battered slopes and graded margins and split turfs	M²	470	3.00	1410.00

TOTAL 20,152 (based on locally won aggregate)

Option 2 Motorised access

ITEM	DESCRIPTION	UNIT	QUANTITY	RATE £	AMOUNT + VAT £
1	Between 5m-63m & 175m-286m reconstruct route of width 2.25m with 950mm as raised sub-base and 25mm graded surfacing compacted to form a 1:40 crossfall draining to ditch.	M	169	35.00	8,870
2	Between 63m-148m & 350m-470m scrape vegetation of width 2.25m and resurface with 75mm as raised subbased and 25mm graded surfacing compacted to form a 1:40 crossfall draining to ditch	M	205	7.00	2,150
3	Between 148m-175m reconstruct route of width 2.25m with 1475mm as raised sub-base and 25mm graded surfacing compacted to form a 1:40 crossfall draining to ditch.	M	27	50.00	2,025
4	Between 286m-350m reconstruct route with 375mm+25mm as above.	М	64	20.00	1,920
5	At 109m and between 263m- 274m rebuild drystone wall to same section and dimensions as existing wall	M	13	100.00	1,300.00
6	Between 160m-175m install retaining wall to retain field edge of height 10.5m	M	15	50.00	750.00
7	At 160m and 175m renovate existing wall ends as necessary to consolidate.	No	2	100.00	200.00
8	Between 64m-148m rebuild burn side revetment as necessary to consolidate.	M^2	20	50.00	1,000.00

ITEM	DESCRIPTION	UNIT	QUANTITY	RATE	AMOUNT + VAT
9	Remove existing culvert pipes in ditch to a licensed tip.	M	34	10.00	340.00
10	Between 0m-324m clear all encroaching vegetation and trees from route and ditch to create a clear walking tunnel of width 4m and height 3m	M	324	0.50	162.00
11	Between 0m-470m clear out/redefine and reprofile ditch sensitively to avoid damage to existing stonework and create a low profile ditch whole appropriate with vegetated sides	M	470	7.00	3290.00
12	At 507m, 1040 and 1180 install 3 no. new culvert pipes (twin walled polyproplyn) of diameter 500mm and length 6m with stone loadwalls	M	18	40.00	720.00
13	At 507, 1040 and 1180 break ditch at culverts with rock arour	M ²	6	50.00	300.00
14	At 5m and 63m remove barrier including field gates and bollards and remove to a licensed tip.	No	2	100.00	200.00
15	Allowance for replacement of new barriers/gates.		Sum		500.00
16	Landscape route margins and disturbed ground with even battered slopes and graded margins and split turfs between 0m-470m	M²	470	3.00	1410.00
					

TOTAL <u>25,147</u> (based on locally won aggregate)

THE E.)	
156 ENDWALL TREE () 8 WETAL	n2
156 ENDWALL TREE () 8 WETAL	n ^y
156 Han-162m D WETAL	n ^y
156 48m-162m 0 V	
The second of th	
1800MM 8	
	Ñ.
148 10901-148M 0 X MILLS BY REVETMENT	
1 1 1 1/13/4 1/13/4 U ' T.A., 1/1 'OCTESSTOCKOS	
ROUTE OK VRUTTIK & REPAIR IOM?	
112	
8'	
109 HOLFIN WALL 8: 64m-109m 2m2 0 01 West Wast	
1 1 1 1 AUGU U 109	
DUTE OK Y RUTING V VENTING VIEW	
I DESCRIPTION OF A 11 CONTRACTOR OF THE PROPERTY OF THE PROPER	
64 BOLLAROS LESTINANG O	
63 METAL FIELD GATE D. ST. FERLE	
Q V METAL.	
52 Sm-63m D V	
BULLDUP 8	
ROUTE Q V 11. Dem	
[]] [[] [] [] [] [] [] [] []	
41 · · · · · · · · · · · · · · · · · · ·	j
2 V 7mx sooyn	
34]
12 \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	ļ
13 1 1 1 2 IM OPEN	
	l
5 1.5M METRY FIELD & ROADSIDE EXTRE	
Com	
BOURRS A NOTAL	
3 KESTRATICA B/ A	
ACCESS Of . A. \ 3m OPEN	
OOOOOOO A HEMP	[
- O GETTINGTH	1
ARPACHIC CORP.	ļ
ARDACHY ROAD	ĺ
T CULLARY CALLERY	1
FAILURE, AT EXIT	
DIST. G P.W. WORK REQUIRED DESCRIPTION	
(m)	
ADDREVIATIONS C. P Com Brown D C. D. D C. D D	

Abbreviations: G.R. = Grid Reference, Dist (m) = Distance in metres, G (0) = Gradient in degrees, P.W. (m) = Path Width in metres

PATH NAMI	E: (DIUK/E	YAIRACK PASS	PATH NO./ SECTION No.: (U/	ACHY COUNT TOTAL PATH LENGTH: 1224
G.R. START	Γ:		G.R. END:	SURVEY SHEET NO: 2
F		1. A Called		
286	 	SKN ON PATY		er en
			веолоск	<u></u>
283		BOLLOWN O		, ···
274		263m-274m 60 WALL FAICING 088		
250	-	175m-286m 0	V (
		ROUTE 1	V 124M OPEN	
236			VA	
224	-	0 0	V V V V V V V V V V V V V V V V V V V	
209		0	v Nan	
		8	V	
2 71		NULLOUP NULLE NEGULUO	V	
162		20m²	v J	
DIST. G (m) (⁰)	P.W. (m)	Work	REQUIRED	DESCRIPTION

Abbreviations: G.R. = Grid Reference, Dist (m) = Distance in metres, $G(^0)$ = Gradient in degrees, P.W. (m) = Path Width in metres

G.R. START: 1224 1180 15 170	PAILED CULUTURE THE PLANE	Coats	ELOCK DITCH WITH BOCK	SURVEY SHEET NO: 3
040	FAILED CULVETU	Coats	Í	्रेड इ
040	FAILED CULVETU	Coats	Í	्रेड इ
040	FAILED CULLUTU	Coats	Í	હેલ્ ^ક
15	FAILED CULLUTU	Coats	Í	
15	FAILED CULLUTU		BLOCK DITCH WITH BOCK	
15	FAILED CULLUTU		WITH BOCK	<i>\$</i>
15	FAILED CULLUTU		31197 1111	
15				
15	FATULO CULU REPUBLIE			
15	FATILLO CULU			
15	FATILLO CULU		i	
15	FATULO CULU TULOURUE	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		
77	FATILLO CIKU		E STY WILL	
77	reprace			
77	(l	8	DITCHOK	
77	1 3	3		
D7	(MIZZ POND)	F		
	PONO	(
	TRACK TO HOUSE			
		- 	MODOLI CIVIDAE	
	POND PIPED TO	ها ام	INDIAU CULUM INTO PIDE EXA DITE A WITHOUT	
0	ACCESS TREACT	ADD 840	XX DITE A WITH BOCK	
0	<u>i</u>	45	WATERTWUGU	
, O	ACCESS TRACK+		,,,,,,,	
	<u> </u>	1.		
	, , ,	1		
	8	1.1		
	PATH OK			
	RESUMERACE 100MM 0	1		
	0			
\$	WBYKE			
	INDYKE	/ 184	M OPEN	
	9	t		
	1	Y		
р	, N			
	286m-359m	V	İ	
	BULLOUP	V		
	INDICTE	VI		
	400mm D	1		
	 	, V		
	1	(4)		
	9	K) REN	NOVE TREE	
	1	V -	,	
	, <i>k</i>	1/ Y	ĺ	
T. G P.W.	() e		I	
$\binom{0}{0}$ (m)	Wonz	REQUIRED		DESCRIPTION

Abbreviations: G.R. = Grid Reference, Dist (m) = Distance in metres, $G(^0)$ = Gradient in degrees, P.W. (m) = Path Width in metres

- RE: Signs Page 1 of 2

David Andrews

From: Robert Brown [rbrown@nts.org.uk]

Sent: 30 October 2003 10:47

To: David Andrews

Subject: RE: Signs

Hi David could you possably write the guys a reffrence just a genral one to cover all the trainees, it will go as extra evidence to there svq. just somthing saying that they worked with you and hamish and what they were dooing basicly, You can just email it to me that will be fine, cheers Bob Brown.

----Original Message-----From: David Andrews To: Robert Brown

Sent: 10/22/2003 9:30 AM

Subject: RE: Signs

Bob

Can we firm up for the installation of the sign on Loch Ness at the Clansman Hotel for next week. I leave the day to you. I will come on site too and can bring the panel and legs.

David

-----Original Message-----

From: Robert Brown [mailto:rbrown@nts.org.uk]

Sent: 22 October 2003 09:25

To: David Andrews Subject: RE: Signs

Hi David, could you send me the details via email for now as i am on and off the hill this week and often out of signal, i can however get in to the office at night. I do need to sort things out fairly soon, so if you have any info it would be good to get it as soon as poss, i apologise for the difficulties in contacting me unfortunately this canot be helped.

Look forward to heering from you soon.
Thanks Bob Brown.
----Original Message---From: David Andrews
To: Rbrown@nts.org.uk
Sent: 20/10/2003 13:15

Subject: Signs

Bob

Thanks for the call. I hope to have a few jobs for you tomorrow to consider.

David

31/10/2003